

16001

T-BOLTS WITH NUT



A DIVISION OF QUICKSCREWS INTERNATIONAL CORP

SPEC SHEET

Part #	Box Quantity	Size
16001	T-Bolts + Nut (100)	3/8" x 1 1/4"



T																						
<p>3/8-16 Hex Serrated Flange Nut</p>		<p>With Knurling Under Head</p>																				
ITEM	d	k	n	m	a(max)	L	Tolerance															
3/8-16	9.25-9.49	4.20-4.50	22.73-23.00	10.03-10.30	4.50	1-1/4"																
MECHANICAL	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%; text-align: center;">16001</td> <td style="width: 80%;">3/8-16 X 1-1/4" T-Bolt SS W/Nut 100/PK</td> <td style="width: 10%;">UNIT</td> <td style="width: 10%;">mm</td> </tr> <tr> <td></td> <td>3/8-16 Hex Serrated Flange Nut</td> <td>Revision</td> <td>Material ANSI 304</td> </tr> <tr> <td></td> <td></td> <td></td> <td>With Knurling</td> </tr> <tr> <td></td> <td></td> <td></td> <td>Under Head</td> </tr> </table>				16001	3/8-16 X 1-1/4" T-Bolt SS W/Nut 100/PK	UNIT	mm		3/8-16 Hex Serrated Flange Nut	Revision	Material ANSI 304				With Knurling				Under Head		
					16001	3/8-16 X 1-1/4" T-Bolt SS W/Nut 100/PK	UNIT	mm														
						3/8-16 Hex Serrated Flange Nut	Revision	Material ANSI 304														
								With Knurling														
			Under Head																			